


Absylux® FR



Absylux® ABS FR is Flame Retardant Acrylonitrile Butadiene Styrene. The material exhibits UL94 V0 flame retardancy performance in thicknesses down to 0.0625”T and excellent dimensional stability, especially as compression molded sheet.

INDUSTRY



Engineering

COLORS AVAILABLE



Black

ATTRIBUTES

 Impact Resistance	<input checked="" type="checkbox"/>
 Dielectric Properties	<input checked="" type="checkbox"/>
 Dimensional Stability	<input checked="" type="checkbox"/>
 Flammability Resistance	<input checked="" type="checkbox"/>

SHAPES

Compression Sheet	<input checked="" type="checkbox"/>
Extruded Sheet	<input checked="" type="checkbox"/>
Extruded Film	<input checked="" type="checkbox"/>
Extruded Rod	<input checked="" type="checkbox"/>

Absylux® FR

TYPICAL PROPERTIES

PROPERTY	TEST STANDARD	ENGLISH UNITS	METRIC UNITS
Mechanical			
Flexural Modulus	D790	339 kpsi	2,340 MPa
Flexural Strength - Yield	D790	9.7 kpsi	67 MPa
Izod Impact, notched	D256	3.99 ft-lb/in	213 J/m
Tensile Elongation @ Break	D638	17 %	17 %
Tensile Elongation @ Yield	D638	2.4 %	2.4 %
Tensile Modulus	D638	298 kpsi	2,060 MPa
Tensile Strength @ Break	D638	4.4 kpsi	30 MPa
Tensile Strength @ Yield	D638	5.4 kpsi	37 MPa
Thermal			
HDT @ 264 psi	D648	167 °F	75 °C
HDT @ 64 psi	D648	186 °F	86 °C
Physical			
Specific Gravity	D792	1.19	1.19

*Data above is based on testing of injection molded test specimens

Absylux® FR

PRODUCT SHAPES & DIMENSIONS

Rods: 48"L (122cm)

2.5" (63.5mm) 2.75" (69.85mm)

Rods: 96"L (244cm)

0.5" (12.7mm) 0.625" (15.88mm) 0.75" (19.05mm) 1" (25.4mm) 1.25" (31.75mm) 1.375" (34.93mm)
 1.5" (38.1mm) 1.625" (41.28mm) 1.75" (44.45mm) 1.875" (47.63mm) 2" (50.8mm)

Compression Sheets: 24"W x 48"L (61cm x 122cm)

0.25" (6.35mm) 0.375" (9.53mm) 0.5" (12.7mm) 0.75" (19.05mm) 1.0" (25.4mm) 1.25" (31.75mm)
 1.5" (38.1mm) 1.75" (44.45mm) 2.0" (50.8mm) 2.25" (57.15mm) 2.5" (63.5mm) 2.75" (69.85mm)
 3.0" (76.2mm) 3.25" (82.55mm) 3.5" (88.9mm) 3.75" (95.25mm) 4.0" (101.6mm) 4.25" (107.95mm)
 4.5" (114.3mm) 4.75" (120.65mm) 5.0" (127mm) 5.25" (133.35mm) 5.5" (139.7mm) 5.75" (146.05mm)
 6.0" (152.4mm)

Compression Sheets: 48"W x 96"L (122cm x 244cm)

0.25" (6.35mm) 0.5" (12.7mm) 0.75" (19.05mm) 1" (25.4mm) 1.25" (31.75mm) 1.50" (38.1mm)
 1.75" (44.45mm) 2" (50.8mm) 2.25" (57.15mm) 2.50" (63.5mm) 2.75" (69.85mm) 3" (76.2mm)
 3.25" (82.55mm) 3.50" (88.9mm) 3.75" (95.25mm) 4" (101.6mm) 4.25" (107.95mm) 4.50" (114.3mm)
 4.75" (120.65mm) 5" (127mm) 5.25" (133.35mm) 5.50" (139.7mm) 5.75" (146.05mm) 6" (152.4mm)

Absylux® FR

Compression Sheets: 48"W x 120"L (122cm x 305cm)

0.25" (6.35mm)	0.375" (9.53mm)	0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)
1.50" (38.1mm)	1.75" (44.45mm)	2" (50.8mm)	2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)
3" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)	3.75" (95.25mm)	4" (101.6mm)	4.25" (107.95mm)
4.50" (114.3mm)	4.75" (120.65mm)	5" (127mm)	5.25" (133.35mm)	5.50" (139.7mm)	5.75" (146.05mm)
6" (152.4mm)					

Compression Sheets: 60"W x 120"L (152cm x 305cm)

0.25" (6.35mm)	0.375" (9.53mm)	0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)
1.50" (38.1mm)	1.75" (44.45mm)	2" (50.8mm)	2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)
3" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)	3.75" (95.25mm)	4" (101.6mm)	4.25" (107.95mm)
4.50" (114.3mm)	4.75" (120.65mm)	5" (127mm)	5.25" (133.35mm)	5.50" (139.7mm)	5.75" (146.05mm)
6" (152.4mm)					

Extruded Sheets: 48"W x 96"L (122cm x 244cm)

0.03" (0.76mm)	0.035" (0.89mm)	0.06" (1.52mm)	0.062" (1.57mm)	0.08" (2.03mm)	0.09" (2.29mm)
0.095" (2.41mm)	0.125" (3.18mm)	0.1875" (4.76mm)	0.25" (6.35mm)		

Extruded Films: 26"W (66cm)

0.01" (0.25mm)	0.02" (0.51mm)
----------------	----------------

LAST REVISED: 09/05/2023

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or other incidental or consequential loss) shall be available to the buyer.

EXCLUSION OF WARRANTIES: THERE ARE NO WARRANTIES AS TO THE MATERIAL DESCRIBED HEREIN, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. ANY VALUES STATED IN SELLER'S LITERATURE ARE TYPICAL PROPERTIES ONLY.