



Pro-fax 6323

LyondellBasell Industries - Polypropylene Homopolymer

Friday, January 24, 2025

General Information

Product Description

Pro-fax 6323 general purpose polypropylene homopolymer is available in pellet form. This resin is typically used in injection molding applications.

ASTM and ISO-based versions of the technical data sheet are available for Pro-fax 6323.

General

Material Status	• Commercial: Active		
Regional Availability	• North America		
Features	• Heat Aging Resistant		
Uses	<ul style="list-style-type: none"> • Automotive Applications • Caps • Closures • Consumer Applications 	<ul style="list-style-type: none"> • Containers • Film • Flexible Packaging • Food Packaging 	<ul style="list-style-type: none"> • Rigid Packaging • Sporting Goods • Toys
Automotive Specifications	• CHRYSLER MS-DB-500 CPN 2571	• CHRYSLER MS-DB-500 CPN2571	
Processing Method	• Cast Film	• Injection Molding	

ASTM & ISO Properties ¹

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Density / Specific Gravity			
--	0.902	0.902	ASTM D792
73°F (23°C)	0.900 g/cm ³	0.900 g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12 g/10 min	12 g/10 min	ASTM D1238
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Strength			
Yield	• 4900 psi	• 33.8 MPa	ASTM D638
	• 4930 psi	• 34.0 MPa	
Yield, 73°F (23°C)	4500 psi	31.0 MPa	ISO 527-2
Tensile Elongation			
Yield	11 %	11 %	ASTM D638
Yield, 73°F (23°C)	11 %	11 %	ISO 527-2
Flexural Modulus			
1% Secant ²	210000 psi	1450 MPa	ASTM D790A
1% Secant ³	210000 psi	1450 MPa	ASTM D790A
73°F (23°C)	187000 psi	1290 MPa	ISO 178

Copyright ©, 2025, Formerra, LLC. All the information in this literature is for general information purpose only. Formerra makes no representations, guarantees, or warranties of any kind with respect to the information contained in this literature, including its accuracy, completeness, reliability, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for pricing, property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Formerra makes no warranties or guarantees respecting suitability of either Formerra's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. FORMERRA MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature or any other provided literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner. Any action you take upon the information you find in this literature is strictly at your own risk. Formerra will not be liable for any losses and/or damages in connection with the use of this literature. By using this literature, you hereby consent to this disclaimer and agree to its terms.

Pro-fax 6323

LyondellBasell Industries - Polypropylene Homopolymer

Impact	Typical Value (English)	Typical Value (SI)	Test Method
Charpy Notched Impact Strength (73°F (23°C))	2.0 ft·lb/in ²	4.2 kJ/m ²	ISO 179
Notched Izod Impact			
73°F (23°C)	• 0.60 • 0.60 ft·lb/in	• 32 • 32 J/m	ASTM D256A
73°F (23°C)	2.0 ft·lb/in ²	4.1 kJ/m ²	ISO 180
Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Deflection Temperature Under Load			
66 psi (0.45 MPa), Unannealed	• 199 °F • 200	• 93.0 °C • 93.3	ASTM D648
66 psi (0.45 MPa), Unannealed	169 °F	76.0 °C	ISO 75-2/B
264 psi (1.8 MPa), Unannealed	120 °F	49.0 °C	ISO 75-2/A

Notes

¹ Typical properties: these are not to be construed as specifications.

² 0.050 in/min (1.3 mm/min)

³ 0.051 in/min (1.3 mm/min)

Copyright ©, 2025, Formerra, LLC. All the information in this literature is for general information purpose only. Formerra makes no representations, guarantees, or warranties of any kind with respect to the information contained in this literature, including its accuracy, completeness, reliability, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for pricing, property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Formerra makes no warranties or guarantees respecting suitability of either Formerra's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. FORMERRA MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature or any other provided literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner. Any action you take upon the information you find in this literature is strictly at your own risk. Formerra will not be liable for any losses and/or damages in connection with the use of this literature. By using this literature, you hereby consent to this disclaimer and agree to its terms.